



Jamb Depth

Smallest jamb depth available for an equal rabbet frame is $5 \frac{1}{4}$ " ($4 \frac{1}{4}$ " Wall Dimension). Smaller jamb depths must be unequal or single rabbet.

Largest jamb depth available for an equal rabbet frame is $52 \frac{7}{8}$ " ($51 \frac{7}{8}$ " Wall Dimension).

Smallest jamb & head face dimension available on a welded or KD equal rabbet frame is $5/8$ ".

On KD frames, the largest jamb face dimension available on equal rabbet frames is 2 ".

On KD equal rabbet frames the largest head face dimension that can be paired to a 2 " or less KD jamb is 4 ".

Largest jamb & head face dimension available on welded equal rabbet frames is $52 \frac{7}{8}$ ". Any combination of head and jamb face dimension is acceptable.

UL Fire Rated equal rabbet frames:

- Smallest jamb & head face dimension allowed is $1 \frac{1}{4}$ "
 - Largest jamb face dimension allowed is 4 "
 - Largest head face dimension allowed is 6 "
 - Largest jamb depth available is 14 "
- 14 Gauge frames do not have $5/16$ " drywall returns.

All fire-rated frames scheduled to be installed as welded frame assemblies **MUST** be welded by J/R Metal Frames in our shop.

 <small>MANUFACTURERS OF STANDARD AND CUSTOM HOLLOW METAL FRAMES AND DOORS</small>			
<small>287 Oakland Road, Belgrade, Maine 04917 USA Office 207-465-9066 Fax: 207-465-9452</small>			
QUALITY SINCE 1981	Title: Masonry Profile		
	Revision:	Revision Date:	Drawing Number:
Original Date:	Drawn By:		Scale: Full Sized
Sheet:		of	