

Smallest jamb depth available for an unequal rabbet frame is 4 3/8" (3 3/8" Wall Dimension). Smaller jamb depths must be single rabbet.

Largest jamb depth available for an unequal rabbet frame is 52 7/8" (51 7/8" Wall Dimension).

Smallest jamb & head face dimension available on a welded or KD unequal rabbet frame is 5/8".

On KD frames, the largest jamb face dimension available on unequal rabbet frames is 2".


On KD unequal rabbet frames the largest head face dimension that can be paired to a 2" or less KD jamb is 4".

Largest jamb & head face dimension available on welded unequal rabbet frames is 52 7/8". Any combination of head and jamb face dimension is acceptable.

UL Fire Rated unequal rabbet frames:

- Smallest jamb & head face dimension allowed is 1 1/4"
- Largest jamb face dimension allowed is 4"
- Largest head face dimension allowed is 6"
- Largest jamb depth available is 14"
- 14 Gauge frames do not have 5/16" drywall returns.

All fire-rated frames scheduled to be installed as welded frame assemblies MUST be welded by J/R Metal Frames in our shop.

			
<small>MANUFACTURERS OF STANDARD AND CUSTOM HOLLOW METAL FRAMES AND DOORS</small>			
<small>287 Oakland Road, Belgrade, Maine 04917 USA Office 207-465-9066 Fax: 207-465-9452</small>			
QUALITY SINCE 1981	Title: Unequal Rabbet Frame		
	<small>Original Date:</small> 03-16-07	<small>Revision:</small> #1	<small>Revision Date:</small> 04-17-07
<small>Drawn By:</small>	<small>Scale:</small> Full Sized	<small>Sheet:</small> 52 of 55	